

# Make Home Ignition Zone Maintenance a Priority

## WHY?

The home ignition zone requires regular, ongoing maintenance to be effective. Your home is located in a dynamic environment — trees, grasses and shrubs continue to grow, die and drop leaves each season, and there are ongoing maintenance needs on any structures on your property.

## HOME IGNITION ZONE CHECKLIST

### PREPARE YOUR HOME FOR WILDFIRE WITH THESE STEPS

#### TOP PRIORITIES

- CLEAR** roof, deck and gutters of pine needles and other debris.\*
- MOW** grass and weeds to a height of 4 inches or less.\*
- RAKE AND REMOVE** all pine needles and other flammable debris from 5 feet around the foundation of your home and deck.\*
- TREAT** or mow shrubs that re-sprout aggressively (such as Gambel oak) every 3-5 years or more depending on growth rates.
- REMOVE** branches that hang over the roof and chimney.
- DISPOSE** of slash from thinning trees and shrubs by chipping, hauling to a disposal site or piling in open areas for burning later. *Any accumulation of slash that's chipped or otherwise should be 30 feet or more from the home.\**
- AVOID** creating continuous areas of wood chips on the ground when chipping logs and/or slash. Break up the layer of wood chips by adding nonflammable material, or allow for wide gaps of at least 3 feet between chip accumulations.

\* Address as needed, more than once a year.

#### FIREWOOD

- Keep firewood stacked uphill from (or at the same elevation as) any structures, and keep the woodpile at least 30 feet away from the home.
- Do not stack firewood between remaining trees, underneath the deck or on the deck.
- Remove flammable vegetation within 10 feet of woodpiles.

#### PROPANE TANKS

- Keep aboveground tanks at least 30 feet from the home, preferably on the same elevation as the house.
- Remove flammable vegetation within 10 feet of all propane tanks and gas meters.

#### DRIVEWAYS

- Maintain at least 10 feet between tree crowns, thinning them a minimum of 30 feet back from each side of the driveway from the house to the main access road.
- Remove ladder fuels beneath trees after thinning.
- Remove any shrubs that are within 10 feet of the outer edge of tree crowns.
- Space shrubs apart at least 2 ½ times their mature height, as measured from the edge of the shrubs.
- Post signs at the end of the driveway with your house number that are noncombustible, reflective and easily visible to emergency responders.

#### SOLUTIONS FOR MANAGING SLASH

- 1** Spread slash and wood chips over a large area to avoid heavy accumulations and large piles. Being close to the ground will help speed decomposition.
- 2** Burn slash piles, but before doing so, always contact your county sheriff's office or local fire department for current information or possible restrictions.
- 3** Lop and scatter slash by cutting it into small pieces (less than 24 inches long) and spreading it over a wide area, to a depth not exceeding 18 inches. Don't scatter material over 4 inches in diameter.